

Pladepanel med vindue

Vores metalplader med integrerede vinduer kombinerer robuste sikkerhedsfunktioner med klart udsyn til processen og opfylder sikkerhedsstandarden EN ISO 25980:2014. De fås i tre bredder og integreres problemfrit i eksisterende X-Guard-systemer, hvilket forbedrer både beskyttelse og driftseffektivitet.

Forbedr sikkerheden og driftseffektiviteten i dine automatiseringsanlæg med vores X-Guard-pladepaneler med integrerede vinduer.

Disse paneler giver robust beskyttelse mod industrielle farer, samtidig med at de giver mulighed for klar procesovervågning, hvilket sikrer både sikkerhed og produktivitet. Vinduerne fås i klar eller farvet plast; den farvede variant er i overensstemmelse med EN ISO 25980:2014-standarderne og beskytter effektivt mod svejseblink.

Panelerne er fremstillet af 0,8 mm tyk metalplade med en 30x20 mm ramme og fabriksmonterede beslag og er designet til at være holdbare og nemme at montere. Standardpanelhøjden er 2200 mm, og standardpanelfarven er sort (RAL 9011), men tilpassede farver tilbydes efter anmodning.

Disse paneler er compatible med eksisterende X-Guard stolper og dørpakker og sikrer problemfri integration i dine nuværende sikkerhedssystemer. For optimal installation anbefaler vi at bruge den medfølgende dæklister for at eliminere mellemrum mellem panel og stolpe.



Improve safety and operational efficiency in your automation facilities with our X-Guard sheet metal panels featuring integrated windows.

These panels provide robust protection against industrial hazards while allowing clear process monitoring, ensuring both safety and productivity. The windows are available in clear or colored plastic; the colored variant complies with EN ISO 25980:2014 standards, effectively guarding against welding flashes.

Constructed from 0.8 mm thick sheet metal with a 30x20 mm frame and factory-fixed brackets, these panels are designed for durability and straightforward assembly. Standard panel heights are 2200 mm and standard panel color is black (RAL 9011), with customized colors offered upon request.

Compatible with existing X-Guard posts and door packages, these panels ensure seamless integration into your current safety systems. For optimal installation, we recommend using the included cover strip to eliminate gaps

between the panel and post.

Modeller

ARTIKLER / BESKRIVELSE	BREDDE (MM)	HØJDE (MM)	SAFETY DISTANCE (MM)	FARVE
 W340-220080 Transparent	800	2200		Graphite Black (RAL 9011)
 W340-220100 Transparent	1000	2200		Graphite Black (RAL 9011)
 W340-220120 Transparent	1200	2200		Graphite Black (RAL 9011)
 W347-220080 Welding Green	800	2200		Graphite Black (RAL 9011)
 W347-220100 Welding Green	1000	2200		Graphite Black (RAL 9011)
 W347-220120 Welding Green	1200	2200		Graphite Black (RAL 9011)

Relaterede produkter



Tildækningsbånd

A cover strip is available which can be used to cover gaps between posts and panels. It comes in heights of 750, 1900 and 2200 mm. Cover strips in black (RAL 9011) are included in the delivery of s...

5 artikler



Fyldningsmetalplader faste/justerbare

An infill sheet metal functions as a filler when a guard needs a certain width. Fixed infill pieces are available for all heights and in 40 and 70 mm widths. The adjustable infill piece covers gaps...

15 artikler