


Fodgængergelænder med høj kollisionsbarriere

Brug Pedestrian + Impact high-barrieren til at beskytte gangbaner mod mellemstore køretøjer, hvor der er en øget risiko for kollisioner i gulvniveau.



Impact test results					
Area of impact	Load	Equivalent to		90° Deflection	Force to fixings
Centre of barrier C - C as below					
2000mm	8000 J	2500 kg 9.1 km/h	5000 kg 6.4 km/h	450mm	17 kN
Posts					
End post	1850 J	2500 kg 4.3 km/h	5000 kg 3 km/h	NA *	11.6 kN
Mid post	2450 J	2500 kg 5 km/h	5000 kg 3.5 km/h	NA *	12.7 kN

* Deflection of posts is equivalent or less than that of the rail/s and is not considered to be critical for product selection. Performance is tested at height of the lowest rail. The post will perform better for lower strikes and deflection.

Modeller

Posts 6 artikler

ARTIKLER / BESKRIVELSE	HØJDE (MM)	LÆNGDE (MM)	CC (MM)	FARVE
 BCC1-116-I1P2 Pedestrian + Impact H hjørne	1160			Zinc Yellow (RAL 1018)
 BCC0-116-I1P2 Pedestrian + Impact H hjørne	1160			Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
 BCM1-116-I1P2 Pedestrian + Impact H midte	1160			Zinc Yellow (RAL 1018)
 BCM0-116-I1P2 Pedestrian + Impact H midte	1160			Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
 BCE1-116-I1P2 Pedestrian + Impact H ende	1160			Zinc Yellow (RAL 1018)
 BCE0-116-I1P2 Pedestrian + Impact H ende	1160			Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)

Impact rails 7 artikler

ARTIKLER / BESKRIVELSE	HØJDE (MM)	LÆNGDE (MM)	CC (MM)	FARVE
 RCI1-027-0050 Impact rail		270	500	Zinc Yellow (RAL 1018)
 RCI1-277-0300 Impact rail		2770	3000	Zinc Yellow (RAL 1018)
 RCI1-227-0250 Impact rail		2270	2500	Zinc Yellow (RAL 1018)
 RCI1-177-0200 Impact rail		1770	2000	Zinc Yellow (RAL 1018)
 RCI1-127-0150 Impact rail		1270	1500	Zinc Yellow (RAL 1018)
 RCI1-077-0100 Impact rail		770	1000	Zinc Yellow (RAL 1018)




RCI1-047-0070
Impact rail

470

700

Zinc Yellow (RAL 1018)


Hand rails 5 artikler

ARTIKLER / BESKRIVELSE	HØJDE (MM)	LÆNGDE (MM)	CC (MM)	FARVE
 RCP1-027-0050 Håndliste		270	500	Zinc Yellow (RAL 1018)
 RCP1-047-0070 Håndliste		470	700	Zinc Yellow (RAL 1018)
 RCP1-077-0100 Håndliste		770	1000	Zinc Yellow (RAL 1018)
 RCP1-127-0150 Håndliste		1270	1500	Zinc Yellow (RAL 1018)
 RCP1-177-0200 Håndliste		1770	2000	Zinc Yellow (RAL 1018)

Gate 1 artikler

ARTIKLER / BESKRIVELSE	HØJDE (MM)	LÆNGDE (MM)	CC (MM)	FARVE
 GCP8-069-0121 Fodgængerlåde, 690-1210 mm				

Relaterede produkter



Fodgængelænder med påkørselsbarriere

Brug Pedestrian + Impact-barrieren til at beskytte gangbaner mod mellemstore køretøjer, hvor der er en øget risiko for kollisioner i gulvniveau. Denne konfiguration er kompatibel med gulvbarrieren....

19 artikler



SIKKERHEDSVÆRN

Fodgængerlåge

Universelt hængslet, selvlukkende og med indstillelig bredde fra 690 mm til 1210 mm.

1 artikler

X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Hand Rails



Width x Height:

68 x 72 mm | 2 11/16" x 2 27/32"

Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:

116 x 220 mm | 4 9/16" x 8 21/32"

Length:

270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Classic

4 connection sides

Width:

200 mm

7 7/8"

Height:

350 -

1160 mm

13 13/16" -

45 11/16"



Essential

2 connection sides

Width:

132 mm

5 3/16"

Height:

620 -

1170 mm

24 7/16" -



46 1/16"



X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding*

* The highest force depends on the C-C. More information is available upon request.



Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight
3600 kg / 7930 lbs



Loaded weight
2700 kg / 5940 lbs



Loaded weight
2100 kg / 4620 lbs

Speed	Load
6 km/h 3.7 mph	5020 J
8 km/h 5 mph	8880 J
12 km/h 7.5 mph	19960 J

Speed	Load
6 km/h 3.7 mph	3770 J
8 km/h 5 mph	6660 J
12 km/h 7.5 mph	14970 J





Speed	Load
6 km/h 3.7 mph	2930 J
8 km/h 5 mph	5180 J
12 km/h 7.5 mph	11670 J

Component Colours

● RAL 1018 ● RAL 9011

Operating temperature

-10°C → 40°C



1. Bollards
2. Impact
3. Impact High
4. Double Impact Low
5. Double Impact High
6. Pedestrian
7. Pedestrian + Impact
8. Pedestrian + Impact High
9. Pedestrian + Double Impact
10. Pedestrian Gate
11. Column Guard
12. Floor Barrier*
13. Essential Bollards
14. Essential Pedestrian 2 rail
15. Essential Pedestrian
16. Essential Pedestrian + Impact High

* The Floor Barrier can be used in combination with configurations: 3, 6, 8 & 9