

One sided two tier bike rack

Our bi-level bike rack is a smart and flexible solution. The modular system allows you to adapt and expand your bike rack over time, depending on your needs and space. Choose from different rail solutions to create the best parking for your business:



Fast skena




- **Fixed rail** - A stable and reliable solution for those who want an installation without moving parts.
- **Short retractable rail** - Helps to position the bike in the right place, providing an orderly and efficient parking.
- **Long pull-out rail with gas spring** - For extra ease of use. The gas spring allows the bikes to be easily lifted and lowered, providing smooth and ergonomic parking.

The modular system allows you to start with a basic model and later add or adjust features as needed. This allows you to create a customized solution that grows and adapts to changing requirements and spaces.




We also offer **special orders** of C/C dimensions, ranging from **C/C 375 mm to C/C 600 mm**, to give you even more flexibility in the design of your bike rack.

Models




Long extendable rail with gas spring 3 articles

ARTICLES / DESCRIPTION	WIDTH (MM)	DEPTH (MM)	CC (MM)	SURFACE TREATMENT	OTHER
 100-22L Min ceiling height 2420	800	2015	400	Hot dip galvanized	Number of bikes 4
 100-33L Min ceiling height 2420	1200	3600	400	Hot dip galvanized	Number of bikes 6
 100-44L Min ceiling height 2420	1600	3600	400	Hot dip galvanized	Number of bikes 8

Fixed rail 3 articles

ARTICLES / DESCRIPTION	WIDTH (MM)	DEPTH (MM)	CC (MM)	SURFACE TREATMENT	OTHER
 300-22L Min. ceiling height 2420	800	1842	400	Hot dip galvanized	Number of bikes 4
 300-33L Min ceiling height 2420	1200	1842	400	Hot dip galvanized	Number of bikes 6
 300-44L Min ceiling height 2420	1600	1842	400	Hot dip galvanized	Number of bikes 8

Short extendable rail 3 articles

ARTICLES / DESCRIPTION	WIDTH (MM)	DEPTH (MM)	CC (MM)	SURFACE TREATMENT	OTHER
 400-22UL Rec. depth & min ceiling height 3600x2420	800	1967	400	Hot dip galvanized	Number of bikes 4
 400-33UL Rec. depth & min ceiling height 3600x2420	1200	1967	400	Hot dip galvanized	Number of bikes 6
 400-44UL Rec. depth & min ceiling height 3600x2420	1600	1967	400	Hot dip galvanized	Number of bikes 8