

X-Lock

X-Lock is a versatile lock system for all accident prevention series. With a door kit, any panel becomes a secure door. It features a mechanical bolt for hinged and sliding doors, requires conscious action to open, and cannot be locked from inside unless a guard-locking switch is added.



X-Lock can be combined with either of the following:

- A padlock is attached to a plate with three holes, accessible only when the guard is open, preventing door closure during maintenance or setting work inside.
- An interlocking guard switch monitors the guard's open/closed position and is required if the guard is opened more than once a week.

If X-Lock is used with a switch featuring guard locking, an emergency unlocking lever or knob must be integrated into the switch. Otherwise it will not be possible to open X-Lock from inside in case of emergency.

Axelent offers different types of switches and actuators for X-Lock. If you wish to use the X-Lock with a Siemens B-614 with emergency unlocking from the inside, a special version of X-Lock must be used.

IMPORTANT INFORMATION FOR X-LOCK ASSEMBLY

When mounting X-Lock do follow Axelent's mounting instructions precisely. Adjust lock, switch and key carefully, so the lock operates easily without any resistance. This is imperative for correct operation.

Models

ARTICLES / DESCRIPTION	POSITION	OTHER
	Left	
	Left	
	Right	
	Right	Image for illustrative purposes only, showing a left-mounted version
	G3059-4	Lock plate for X-lock