




# Protector de columna grande

Axellent ofrece una protección de columna más grande para ofrecer la protección más flexible para columnas más grandes. Esta protección es adecuada para columnas cuadradas de 400 mm como estándar. También hay rellenos disponibles para ampliar la protección hasta 1000 mm cuadrados. La protección de la columna está fabricada en polietileno de baja densidad para otorgarle alta flexibilidad y resistencia.



## Modelos

ARTÍCULOS / DESCRIPCIÓN	ANCHURA (MM)	ALTURA (MM)
 <b>AG-CP4-110IN</b> Infill, RAL 1003	110	
 <b>AG-CP4-250IN</b> Infill, RAL 1003	250	
 <b>AG-CP400</b> RAL 1003	200	1080



### X-Protect components

These are the building blocks of our modular Impact Protection range.

#### BARRIERS & RAILS

##### Pedestrian Rails



Width x Height:

68 x 72 mm | 2 11/16" x 2 27/32"

Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

##### Impact Barriers



Width x Height:

116 x 220 mm | 4 9/16" x 8 21/32"

Length:

270 - 2770 mm | 10 5/8" - 109 1/16"

#### POSTS & BOLLARDS

**Classic**  
 4 connection sides

Height: 350 – 1160 mm  
 Width: 200 mm  
 13 13/16" – 7 7/8" – 45 11/16"

**Essential**  
 2 connection sides

Height: 620 – 1170 mm  
 Width: 132 mm  
 24 7/16" – 5 3/16" – 46 1/16"

### X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding\*

\* The highest force depends on the C-C. More information is available upon request.



### Impact testing

This is how we calculate the energy from a vehicle impact.


Speed	Load	Speed	Load	Speed	Load
6 km/h   3.7 mph	5020 J	6 km/h   3.7 mph	3770 J	6 km/h   3.7 mph	2930 J
8 km/h   5 mph	8880 J	8 km/h   5 mph	6660 J	8 km/h   5 mph	5180 J
12 km/h   7.5 mph	19960 J	12 km/h   7.5 mph	14970 J	12 km/h   7.5 mph	11670 J

#### Component Colours

● RAL 1018 ● RAL 9011

#### Operating temperature

-10°C → 40°C



#### 1. Bollards

- Classic | 5220 J
- Essential | 1500 J

#### 2. Impact Barriers

- Impact | 4500 J
- Impact High | 6200 J
- Double Impact Low | 7700 J
- Double Impact High | 7000 J

#### 3. Pedestrian Rails

- Pedestrian | 5000 J
- Essential Pedestrian | 2250 J
- Essential Pedestrian 2 rail | 1700 J
- Essential Pedestrian | 2250 J

#### 4. Floor Barrier | 2250 J

- Can be used both with Impact & Pedestrian configurations or as stand-alone protection.

#### 5. Pedestrian Rails + Impact Barriers

- Pedestrian + Impact | 6700 J
- Pedestrian + Impact High | 8000 J
- Pedestrian + Double Impact | 8300 J
- Essential Pedestrian + Impact High | 3100 J

#### 6. Pedestrian Gate | 0 J

#### 7. Column Guard | 1800 J

#### 8. Topple Barriers

- Pedestrian | 5250 J
- Impact | 6200 J

#### 9. Dock Gate | 10200 J

#### 10. Height Restrictors

- Goal Post | 4200 J
- Height Guard

#### 11. Upright Protector