Panneaux acrylique

La gamme X-Guard comprend également des panneaux acrylique en PETG transparent. Certains environnements nécessitent une protection plus complète, que nos cloisons en plastique transparentes peuvent fournir.

Les panneaux acrylique X-Guard sont faciles à installer et vous pouvez utiliser les mêmes poteaux et kits de portes que pour nos autres produits X-Guard. Pour éviter tout écart entre le panneau et le poteau, nous vous recommandons d'installer la bande de protection fournie avec le panneau en plastique. Nos panneaux en plastique peuvent résister à des températures allant jusqu'à 60 degrés et sont disponibles en plastique transparent.



Improve workplace safety with X-Guard plastic panels, a versatile safety fence solution designed for industrial safety applications. Made from durable, impact-resistant plastic, these panels effectively guard against small flying objects, accidental collisions, and chemical exposure, promoting a secure working environment. Their lightweight design allows for easy installation and repositioning, while their transparent material provides clear visibility of automated processes.

Ideal for industries requiring strict hygiene standards, X-Guard plastic panels are easy to clean and resistant to bacterial buildup, making them a smart choice for food processing and pharmaceutical facilities. Designed to integrate seamlessly with X-Guard posts and door systems, these panels offer a cost-effective alternative to traditional metal guarding solutions.

Built to withstand temperatures up to 60°C, X-Guard plastic panels combine strength, flexibility, and efficiency—ensuring optimal machine safety without compromising productivity. For more protection, install the included cover strip to eliminate gaps between the panel and post.

Modèles

Hauteur 750 mm 6 articles

ARTICLES / DESCRIPTION	LARGEUR (MM)	HAUTEUR (MM)	COULEUR
 **W348-075025** PC - transparent	250	750	
 **W348-075040** PC - transparent	400	750	
 **W348-075080** PC - transparent	800	750	
 **W348-075100** PC - transparent	1000	750	
 **W348-075120** PC - transparent	1200	750	
 **W348-075150** PC - transparent	1500	750	

Hauteur 2200 mm 6 articles

ARTICLES / DESCRIPTION	LARGEUR (MM)	HAUTEUR (MM)	COULEUR
 **W348-220025** PC - transparent	250	2200	
 **W348-220040** PC - transparent	400	2200	
 **W348-220080** PC - transparent	800	2200	
 **W348-220100** PC - transparent	1000	2200	
 **W348-220120** PC - transparent	1200	2200	
 **W348-220150** PC - transparent	1500	2200	


Produits associés



Couvre-joint ajustable

Une tôle de remplissage sert de remplissage lorsqu'un panneau a besoin d'une certaine largeur. Les pièces de remplissage fixes sont disponibles pour toutes les hauteurs et en largeurs de 40 et 70 m...

15 articles



Couvre-joint pour panneaux tôlés

Ce système de couvre-joint peut être utilisée pour couvrir les espaces entre les poteaux et les panneaux. Il existe en hauteurs de 750, 1900 et 2200 mm. Le couvre-joint pour panneaux tôlés existe...

5 articles