
Inserto in lamiera

Inserto da utilizzare quando per il cliente è importante che il riparo abbia una larghezza specifica. Sono disponibili inserti per tutte le altezze e per due larghezze differenti. La versione standard è RAL 9011. Tuttavia, può essere adattata ai requisiti del cliente.



The X-Guard infill sheet metal is designed to close gaps in machine guarding panels, ensuring a safe and seamless fit in industrial safety applications. Whether a fixed or adjustable width is required, these infill pieces help create a complete barrier without excessive panel cutting.




Fixed infill pieces are available for all standard heights in 40 mm and 70 mm widths. For greater flexibility, the adjustable infill piece covers gaps ranging from 40 mm to 145 mm, making it easier to adapt to different guard widths.

Thanks to the 100 mm interval between X-Guard panels, the need for custom cutting is significantly reduced, simplifying installation. The infill pieces come in RAL 9011 (black) as standard, with other colors available upon request.

Ideal for machine guarding systems, these infill panels help maintain a professional and safe environment while ensuring compliance with industrial safety standards.

Modelli

Tampone fisso in lamiera 10 articoli

ARTICOLI / DESCRIZIONE	LARGHEZZA (MM)	ALTEZZA (MM)
 **T02-3-07504**	40	750
 **T02-3-07507**	70	750
 **T02-3-13004**	40	1300
 **T02-3-13007**	70	1300
 **T02-3-19004**	40	1900
 **T02-3-19007**	70	1900
 **T02-3-22004**	40	2200
 **T02-3-22007**	70	2200
 **T02-3-24004**	40	2400
 **T02-3-24007**	70	2400

Tampone regolabile in lamiera 5 articoli

ARTICOLI / DESCRIZIONE	LARGHEZZA (MM)	ALTEZZA (MM)
 **T05-3-07515** 40-145 mm		750
 **T05-3-13015** 40-145 mm		1300

	**T05-3-19015** 40-145 mm	1900
	**T05-3-22015** 40-145 mm	2200
	**T05-3-24015** 40-145 mm	2400