Barriera pedonale con impatto alto

Utilizzare la configurazione della Barriera pedonale + Barriera di impatto alta per proteggere le passerelle dai veicoli di medie dimensioni in cui vi sia un rischio ridotto di impatti a livello del suolo.



X-Protect è un approccio unico alle barriere di sicurezza. Modularità senza pari utilizzando solo pochi componenti di sistema e lo smorzamento integrato per creare un sistema a barriera che si adatta al posto di lavoro. X-Protect consente attività rapide di trasformazione, riparazione o sostituzione delle barriere esistenti e le configurazioni su misura sono illimitate.

Risultati dei test di impatto					
Area dell'impatto	*Forza*	*Equivalente a*		*Deflessione a 90°*	*Forza sui fissaggi*
Centro della barriera C - C come sotto					
2000mm	8000 J	2500 kg 9.1 km/h	5000 kg 6.4 km/h	436 mm	5.5 kN
Montanti					
Estremità	1850 J	2500 kg 4.4 km/h	5000 kg 3.1 km/h	NA *	11.6 kN
Area centrale	1850 J	2500 kg 4.4 km/h	5000 kg 3.1 km/h	NA *	12.7 kN

*La deflessione dei montanti è equivalente o inferiore a quella della/e barriera/e e non è considerata critica ai fini della selezione del prodotto. Le prestazioni sono testate all'altezza della barriera più bassa. Il montante offrirà prestazioni migliori in caso di urti a quota inferiore e la deflessione risulterà ridotta.

Modelli

Posts 3 articoli

ARTICOLI / DESCRIZIONE		ALTEZZA (MM)	LUNGHEZZA (MM)	CC (MM)	COLORE
	**BCC0-116-I1P2** Pedestrian + Impact High corner	1160			Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
	**BCM0-116-I1P2** Pedestrian + Impact High mid	1160			Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
	**BCE0-116-I1P2** Pedestrian + Impact High end	1160			Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)

Impact rails 7 articoli

ARTICOLI / DESCRIZIONE		ALTEZZA (MM)	LUNGHEZZA (MM)	CC (MM)	COLORE
	**RCI1-027-0050** Impact rail		270	500	Zinc Yellow (RAL 1018)
	**RCI1-047-0070** Impact rail		470	700	Zinc Yellow (RAL 1018)
	**RCI1-077-0100** Impact rail		770	1000	Zinc Yellow (RAL 1018)
	**RCI1-277-0300** Impact rail		2770	3000	Zinc Yellow (RAL 1018)
	**RCI1-127-0150** Impact rail		1270	1500	Zinc Yellow (RAL 1018)
	**RCI1-177-0200** Impact rail		1770	2000	Zinc Yellow (RAL 1018)

	**RCI1-227-0250** Impact rail		2270	2500	Zinc Yellow (RAL 1018)

Hand rails 5 articoli

ARTICOLI / DESCRIZIONE		ALTEZZA (MM)	LUNGHEZZA (MM)	CC (MM)	COLORE
	**RCP1-027-0050** Hand rail		270	500	Zinc Yellow (RAL 1018)
	**RCP1-047-0070** Hand rail		470	700	Zinc Yellow (RAL 1018)
	**RCP1-077-0100** Hand rail		770	1000	Zinc Yellow (RAL 1018)
	**RCP1-127-0150** Hand rail		1270	1500	Zinc Yellow (RAL 1018)
	**RCP1-177-0200** Hand rail		1770	2000	Zinc Yellow (RAL 1018)

Gate 1 articoli

ARTICOLI / DESCRIZIONE		ALTEZZA (MM)	LUNGHEZZA (MM)	CC (MM)	COLORE
	**GCP8-069-0121** Pedestrian gate, 690-1210 mm				

Prodotti correlati



X-PROTECT PEDESTRIAN

Cancello pedonale

Universale, con chiusura automatica e larghezza regolabile tra 690 mm e 1210 mm.

1 articoli



Barriere pedonali

Utilizzare la configurazione della Barriera pedonale per definire i percorsi pedonali e proteggere da impatti leggeri.

9 articoli



Barriera pedonale con impatto

Utilizzare la configurazione della Barriera pedonale + Barriera di impatto per proteggere le passerelle dai veicoli di medie dimensioni in cui vi sia un rischio maggiore di impatti a livello del su...

16 articoli

Technical Information

X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Pedestrian Rails



Width x Height:
68 × 72 mm | 2 11/16" × 2 27/32"
Length:
270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:
116 × 220 mm | 4 9/16" x 8 21/32"
Length:
270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Classic
4 connection sides
Width:
200 mm
7 7/8"
Height:
350 – 1160 mm
13 13/16" – 45 11/16"

Essential
2 connection sides
Width:
132 mm
5 3/16"
Height:
620 – 1170 mm
24 7/16" – 46 1/16"



X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding*

* The highest force depends on the C-C. More information is available upon request.

























Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight
3600 kg / 7930 lbs

Speed	Load
6 km/h | 3.7 mph	5020 J
8 km/h | 5 mph	8880 J
12 km/h | 7.5 mph	19960 J



Loaded weight
2700 kg / 5940 lbs

Speed	Load
6 km/h | 3.7 mph	3770 J
8 km/h | 5 mph	6660 J
12 km/h | 7.5 mph	14970 J



Loaded weight
2100 kg / 4620 lbs

Speed	Load
6 km/h | 3.7 mph	2930 J
8 km/h | 5 mph	5180 J
12 km/h | 7.5 mph	11670 J

Component Colours

RAL 1018 RAL 9011

Operating temperature

-10°C → 40°C



1. **Bollards**
   - Classic | 5220 J
   - Essential | 1500 J
2. **Impact Barriers**
   - Impact | 4500 J
   - Impact High | 6200 J
   - Double Impact Low | 7700 J
   - Double Impact High | 7000 J
3. **Pedestrian Rails**
   - Pedestrian | 5000 J
   - Essential Pedestrian | 2250 J
   - Essential Pedestrian 2 rail | 1700 J
   - Essential Pedestrian | 2250 J
4. **Floor Barrier** | 2250 J
   - Can be used both with Impact & Pedestrian configurations or as stand-alone protection.
5. **Pedestrian Rails + Impact Barriers**
   - Pedestrian + Impact | 6700 J
   - Pedestrian + Impact High | 8000 J
   - Pedestrian + Double Impact | 8300 J
   - Essential Pedestrian + Impact High | 3100 J
6. **Pedestrian Gate** | 0 J
7. **Column Guard** | 1800 J
8. **Topple Barriers**
   - Pedestrian | 5250 J
   - Impact | 6200 J
9. **Dock Gate** | 10200 J
10. **Height Restrictors**
    - Goal Post | 4200 J
    - Height Guard
11. **Upright Protector**