


シートメタルパネル

X-Guardシリーズでは、金属製の「シートメタルパネル」をご利用いただけます。
視認性を抑えつつ、広範囲にわたる確実な保護を実現します。

取り付けは簡単で、他のX-Guard製品と共通のポストやドアソリューションをそのまま使用可能です。
また、パネルとポストの隙間をなくすために、オプションのカバーストリップを取り付けることもできます。

[安全柵パネルの製品一覧を見る](#)








In automation facilities, ensuring the safety of personnel and equipment is paramount. Our X-Guard sheet metal guarding panels are engineered to provide robust protection against hazards such as moving parts and flying debris, effectively preventing accidental contact and enhancing workplace safety. Constructed from high-quality materials, these panels are durable and capable of withstanding significant impacts, ensuring long-term reliability.

Beyond safety, they offer privacy by concealing sensitive processes, thereby reducing visual distractions and safeguarding proprietary operations. An added benefit is noise reduction, as the solid construction helps to dampen sound, contributing to a quieter and more comfortable working environment. Our standard panels stand at 2200 mm in height, with an optional 750 mm extension for increased coverage. For facilities with specific requirements, we also offer panels in heights of 1900 mm and 2400 mm upon request, providing flexibility to accommodate diverse operational needs.






X-Guard sheet metal panels are easy to fit and you can use the same posts and door packages as for our other machine guarding products. To avoid gaps between the panel and post we recommend you to fit the Cover strip included with the sheet metal panel.

モデル


高さ750 mm 5 品目

品目 / 本製品について	幅 (MM)	高さ (MM)	色
 W349-075025	250	750	Graphite Black (RAL 9011)
 W349-075040	400	750	Graphite Black (RAL 9011)
 W349-075080	800	750	Graphite Black (RAL 9011)
 W349-075100	1000	750	Graphite Black (RAL 9011)
 W349-075120	1200	750	Graphite Black (RAL 9011)

高さ2200 mm 5 品目

品目 / 本製品について	幅 (MM)	高さ (MM)	色
 W349-220025	250	2200	Graphite Black (RAL 9011)
 W349-220040	400	2200	Graphite Black (RAL 9011)
 W349-220080	800	2200	Graphite Black (RAL 9011)
 W349-220100	1000	2200	Graphite Black (RAL 9011)
 W349-220120	1200	2200	Graphite Black (RAL 9011)

関連製品



カバーストリップ

ポストとパネルの間の隙間をカバーするカバーストリップをご用意しています。高さは750、1900、2200 mmからお選びいただけます。ブラックのカバーストリップ(RAL 9011)は、シートメタルおよびプラスチックパネルの納品時に同梱されています。

5 品目



固定 / 調節式インフィルシートメタル

インフィルシートメタルは、ガードに一定の幅が必要な場合の隙間を埋めます。固定式インフィルは、すべての高さに対応し、幅は40 mmと70 mmをご用意しています。調節式インフィルは、40 mmから145 mmの隙間をカバーし、より高い柔軟性を提供します。Axelentのパネル間の間隔は100 mmであり、ランダムな隙間を埋めるためにパネルをカットする手間を削減します。標準カラーはブラック(RA...

15 品目