

# ラージコラムガード

ラージコラムガードは、大型の柱や構造柱をフォークリフトなどの衝突から保護する、大型柱向けコラムガードです。

標準で400mm角の柱に対応し、専用インフィルを追加することで最大1,000mm角まで保護範囲を拡張できます。低密度ポリエチレン製のため、高い柔軟性と耐久性を兼ね備え、衝撃を吸収・分散しながら柱や設備へのダメージを軽減します。

コラムガードの製品一覧を見る



## モデル

| 品目 / 本製品について | | 幅 (MM) | 高さ (MM) |
|---|---|---|---|
|  | **AG-CP4-110IN**<br>Infill, RAL 1003 | 110 | |
|  | **AG-CP4-250IN**<br>Infill, RAL 1003 | 250 | |
|  | **AG-CP400**<br>RAL 1003 | 200 | 1080 |

X-PROTECT

# Technical Information

## X-Protect components

These are the building blocks of our modular Impact Protection range.

### BARRIERS & RAILS

**Pedestrian Rails**



Width x Height:
68 × 72 mm | 2 11/16" × 2 27/32"
Length:
270 - 1770 mm | 10 5/8" - 69 11/16"

**Impact Barriers**



Width x Height:
116 × 220 mm | 4 9/16" x 8 21/32"
Length:
270 - 2770 mm | 10 5/8" - 109 1/16"

### POSTS & BOLLARDS



**Classic**
4 connection sides
Width:
200 mm
7 7/8"
Height:
350 – 1160 mm
13 13/16" – 45 11/16"


**Essential**
2 connection sides
Width:
132 mm
5 3/16"
Height:
620 – 1170 mm
24 7/16" – 46 1/16"




## X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding*

* The highest force depends on the C-C. More information is available upon request.





## Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight
**3600 kg / 7930 lbs**

| Speed | Load |
|---|---|
| 6 km/h \| 3.7 mph | 5020 J |
| 8 km/h \| 5 mph | 8880 J |
| 12 km/h \| 7.5 mph | 19960 J |



Loaded weight
**2700 kg / 5940 lbs**

| Speed | Load |
|---|---|
| 6 km/h \| 3.7 mph | 3770 J |
| 8 km/h \| 5 mph | 6660 J |
| 12 km/h \| 7.5 mph | 14970 J |



Loaded weight
**2100 kg / 4620 lbs**

| Speed | Load |
|---|---|
| 6 km/h \| 3.7 mph | 2930 J |
| 8 km/h \| 5 mph | 5180 J |
| 12 km/h \| 7.5 mph | 11670 J |

**Component Colours**

RAL 1018 RAL 9011

**Operating temperature**

-10°C → 40°C

1. **Bollards**
   - Classic | 5220 J
   - Essential | 1500 J
2. **Impact Barriers**
   - Impact | 4500 J
   - Impact High | 6200 J
   - Double Impact Low | 7700 J
   - Double Impact High | 7000 J
3. **Pedestrian Rails**
   - Pedestrian | 5000 J
   - Essential Pedestrian | 2250 J
   - Essential Pedestrian 2 rail | 1700 J
   - Essential Pedestrian | 2250 J
4. **Floor Barrier** | 2250 J
   - Can be used both with Impact & Pedestrian configurations or as stand-alone protection.
5. **Pedestrian Rails + Impact Barriers**
   - Pedestrian + Impact | 6700 J
   - Pedestrian + Impact High | 8000 J
   - Pedestrian + Double Impact | 8300 J
   - Essential Pedestrian + Impact High | 3100 J
6. **Pedestrian Gate** | 0 J
7. **Column Guard** | 1800 J
8. **Topple Barriers**
   - Pedestrian | 5250 J
   - Impact | 6200 J
9. **Dock Gate** | 10200 J
10. **Height Restrictors**
    - Goal Post | 4200 J
    - Height Guard
11. **Upright Protector**