


Protection de colonne réglable

Protecteur de colonne unique en son genre, fabriqué à partir d'un polyéthylène basse densité très flexible et résistant. Fourni en quatre sections avec des traverses en plastique qui peuvent être coupées pour s'adapter au site, avec des tailles de 200 mm à 700 mm. Le protecteur de colonne est facile à assembler et ne nécessite aucune fixation au sol. Des vis en acier inoxydable sont fournies en standard.



Modeller

ARTIKELN / BESCHREIWUNG



AG-CPU700
RAL 1003

Zesammenhang Produiten



X-PROTECT BOLLARDS

Poteaux antichocs

Les Poteaux antichocs protègent les coins, les portes et les équipements des impacts de véhicules. Le schéma de couleurs noir et jaune améliore la visibilité et aide à diriger le trafic de chariots...

[7 artikelen](#)



NEW

PROTECTION VERTICALE

Protecteur de montants

Le protecteur de montants permet de protéger les montants des rayonnages contre les chocs causés par les chariots élévateurs et les transpalettes dans les entrepôts très fréquentés. Sa conception a...

[3 artikelen](#)



GARDE-COLONNES

X-Protect Protection de pilier

Pour protéger les piliers de votre installation contre les chocs et les préserver des dommages. De conception unique, la protection est pourvue de cavités spécialement formées pour efficacement dis...

[1 artikelen](#)

X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Pedestrian Rails



Width x Height:

68 x 72 mm | 2 11/16" x 2 27/32"

Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:

116 x 220 mm | 4 9/16" x 8 21/32"

Length:

270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Classic

4 connection sides

Height:

350 -

Width:

200 mm

13 13/16" -

7 7/8"

45 11/16"



Essential

2 connection sides

Height:

620 -

Width:

132 mm

5 3/16"

1170 mm

24 7/16" -






46 1/16"



X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding*

* The highest force depends on the C-C. More information is available upon request.



$$E_k = \frac{mv^2}{2}$$

E_k = kinetic energy (truck motion energy) [J]

m = truck weight [kg/lbs]

v = truck speed [km/h or mph]

Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight

3600 kg / 7930 lbs



Loaded weight

2700 kg / 5940 lbs



Loaded weight

2100 kg / 4620 lbs

Speed	Load
6 km/h 3.7 mph	5020 J
8 km/h 5 mph	8880 J
12 km/h 7.5 mph	19960 J

Speed	Load
6 km/h 3.7 mph	3770 J
8 km/h 5 mph	6660 J
12 km/h 7.5 mph	14970 J


Speed	Load
6 km/h 3.7 mph	2930 J
8 km/h 5 mph	5180 J
12 km/h 7.5 mph	11670 J

Component Colours

● RAL 1018 ● RAL 9011

Operating temperature

-10°C → 40°C



1. Bollards

- Classic | 5220 J
- Essential | 1500 J

2. Impact Barriers

- Impact | 4500 J
- Impact High | 6200 J
- Double Impact Low | 7700 J
- Double Impact High | 7000 J

3. Pedestrian Rails

- Pedestrian | 5000 J
- Essential Pedestrian | 2250 J
- Essential Pedestrian 2 rail | 1700 J
- Essential Pedestrian | 2250 J

4. Floor Barrier | 2250 J

- Can be used both with Impact & Pedestrian configurations or as stand-alone protection.

5. Pedestrian Rails + Impact Barriers

- Pedestrian + Impact | 6700 J
- Pedestrian + Impact High | 8000 J
- Pedestrian + Double Impact | 8300 J
- Essential Pedestrian + Impact High | 3100 J

6. Pedestrian Gate | 0 J

7. Column Guard | 1800 J

8. Topple Barriers

- Pedestrian | 5250 J
- Impact | 6200 J

9. Dock Gate | 10200 J

10. Height Restrictors

- Goal Post | 4200 J
- Height Guard

11. Upright Protector