

TECHNICAL INFORMATION X-GUARD®

Product fact material X-Guard®			
Product	Dimension (mm)	Standards	Additional information
Posts	50x50x1,5 eller 50x100x1,5	SS1312/EN235+CR1, EN 10305-5	
Base plate	145x55x6	S600MC	
Panel	Upright 30x20x1,25 mm	SS1312/EN235+CR1, EN 10305-5	
	Horizontals 25x15x1 mm	SS1312/EN235+CR1, EN 10305-5	
Wire	Vertical Dia 3mm	C9D 1312	
	Horizontals Dia 2,5 mm	C9D 1312	
Accident prevention	Plastic 2 mm	Thermoplastic polyester	
	Sheet metal 0,8 mm	DIN 1623, EN 10130, DC01	Tenac POM-Copolymer.pdf
Panel Quick Fittings	Upper housing plastic	POM Tenac C 3510	Hostacom G2 U02.pdf
	Lower housing plastic (cover steel plate)	PP Hostacom G2U02	
Post top plug	Plastic	Moplen EP300K	SKMBT C45109062414440
Post base plate cover	Plastic	PC/ABS45FS	Hostacom G2 U02.pdf
Fittings for top rail (hinge doors)	Plastic	PP Hostacom G2U02	
Door sliding support	Plastic	Hostacom G2 N02 (PP20%GF)	Hostacom_Broschyr 2006.pdf

Cleaning: To clean use water and a light detergent and rinse off with lukewarm water. The excess water can be dried with a lint-free cotton cloth. Abrasives, wire brush, scouring pad, or other products with abrasive effects may not be used. Avoid drying with paper that easily scratches.

OPERATING AND MAINTENANCE INSTRUCTIONS					
CLEANING	PERFORMED X NUMBER OF TIMES A			IN CASE	ANNEX
	WEEK	MONTH	YEAR		
				X	

Improvement of colour can be made if necessary. Extra spray paint can be purchased from Axelent AB.

NOTE! Axelent mesh, plastic and sheet steel panels must not be stored outdoors or in humid conditions where the risk of rust is present.

CONTACT INFO

Axelent AB, Box 1, SE-330 33 Hillerstorp
+46 (0)370-37 37 37, teamyellow@axelent.se
www.axelent.com