

Topple Barrier Pedestrian

The X-Protect Topple Barrier Pedestrian helps create safe separation between storage areas, pedestrian walkways and internal traffic routes in warehouse and logistics environments. Designed to maintain visibility and efficient workflow, the system helps providing clear segregation between traffic and personnel.



The X-Protect Topple Barrier Pedestrian is developed for warehouse, logistics and production environments where pallet handling, stored goods and internal traffic create safety risks for personnel and operations.

Topple Barrier Pedestrian provide clear segregation and protect personnel from leaning or falling goods while maintaining open visibility across the workspace. Its modular construction integrates directly with the X-Protect range, allowing flexible and continuous protection layouts throughout the facility.

The flexible design enables safe and efficient workflows in busy operational environments. Installation is fast and straightforward using the same simple installation approach as the rest of the X-Protect range, allowing damaged sections to be replaced quickly when needed.

Key features

- Modular X-Protect integration

- Fast and easy to install
- Easy to repair
- Maintains visibility and workflow
- Flexible and scalable design

Impact test results

	Area of impact	Load		Equivalent to	90° deflection	Force to fixings
	Centre of barrier C - C as below					
Topple Barrier Pedestrian 2300	2000 mm	5000 J	2500 kg 7,2 km/h	5000 kg 5,1 km/h	N/A	10,1 kN
	Post					
Topple Barrier Pedestrian 2300	End post	5250 J	2500 kg 7,3 km/h	5000 kg 5,2 km/h	N/A	7,5 kN
Topple Barrier Pedestrian 2300	Mid post	5250 J	2500 kg 7,3 km/h	5000 kg 5,2 km/h	N/A	5,8 kN
	Area of impact	Load		Equivalent to	90° deflection	Force to fixings
	Centre of barrier C - C as below					
Topple Barrier Pedestrian 3400	2000 mm	5000 J	2500 kg 7,2 km/h	5000 kg 5,1 km/h	N/A	5,3 kN
	Post					
Topple Barrier Pedestrian 3400	End post	5250 J	2500 kg 7,3 km/h	5000 kg 5,2 km/h	N/A	7,2 kN
Topple Barrier Pedestrian 3400	Mid post	5250 J	2500 kg 7,3 km/h	5000 kg 5,2 km/h	N/A	9,9 kN

* Deflection of posts is equivalent or less than that of the rail/s and is not considered to be critical for product selection. Performance is tested at height of the lowest rail. The post will perform better for lower strikes and deflection. The Axelent Topple Barrier is tested for static load on top rail up to 400 kg.

Models

Height 2300 mm 4 articles

ARTICLES / DESCRIPTION		WIDTH (MM)	HEIGHT (MM)	COLOR
	BTC0-228-00P6 Topple Pedestrian corner		2300	Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
	BTE0-228-00P6 Topple Pedestrian end		2300	Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
	BTM0-228-00P6 Topple Pedestrian mid		2300	Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)



BTT0-228-00P6
Topple Pedestrian T post

2300

Zinc Yellow (RAL 1018)
Graphite Black (RAL 9011)

Height 3400 mm 4 articles

ARTICLES / DESCRIPTION	WIDTH (MM)	HEIGHT (MM)	COLOR
 BTC0-340-00P9 Topple Pedestrian corner		3400	Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
 BTE0-340-00P9 Topple Pedestrian end		3400	Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
 BTM0-340-00P9 Topple Pedestrian mid		3400	Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)
 BTT0-340-00P9 Topple Pedestrian T post		3400	Zinc Yellow (RAL 1018) Graphite Black (RAL 9011)

Hand rails 5 articles

ARTICLES / DESCRIPTION	WIDTH (MM)	HEIGHT (MM)	COLOR
 RCP1-047-0070 Hand rail			Zinc Yellow (RAL 1018)
 RCP1-077-0100 Hand rail			Zinc Yellow (RAL 1018)
 RCP1-127-0150 Hand rail			Zinc Yellow (RAL 1018)
 RCP1-177-0200 Hand rail			Zinc Yellow (RAL 1018)
 RCP1-027-0050 Hand rail			Zinc Yellow (RAL 1018)

Related products



COLUMN GUARDS

Multifunction Column Guard

The Multifunction Column Guard is designed to protect large building columns and pillars from impacts caused by forklifts and other material handling equipment. With asymmetrical on-site adjustment...

[3 articles](#)



CLASSIC PEDESTRIAN

Pedestrian Barrier

Use the X-Protect Pedestrian Barrier configuration to define pedestrian routes and protect from light duty impacts. It is also possible to combine with a pedestrian gate. The pedestrian gate is sel...

[9 articles](#)



IMPACT PROTECTION

Floor Barrier

Designed to serve as a standalone solution, it provides safeguarding of building perimeters and vital infrastructure from the everyday risks of vehicle forks, pallets in transit, AMRs and AGVs, and...

[11 articles](#)



X-PROTECT DOCK GATE

Dock Gate

The X-Protect Dock Gate helps protect loading bays and dock areas in demanding warehouse and logistics environments. Designed for smooth and controlled operation, it combines reliable impact protec...

[3 articles](#)

NEW



X-PROTECT BOLLARDS

Bollards

X-Protect Bollards safeguard corners, doorways and equipment from vehicle impacts. The black and yellow colour scheme enhances visibility and helps direct forklift traffic, creating safer, well-org...

[7 articles](#)

X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Pedestrian Rails



Width x Height:

68 x 72 mm | 2 11/16" x 2 27/32"

Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:

116 x 220 mm | 4 9/16" x 8 21/32"

Length:

270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Classic

4 connection sides

Height:

350 -

Width:

200 mm

13 13/16" -

7 7/8"

45 11/16"



Essential

2 connection sides

Height:

620 -

Width:

132 mm

5 3/16"

24 7/16" -







46 1/16"



X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding*

* The highest force depends on the C-C. More information is available upon request.




Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight

3600 kg / 7930 lbs



Loaded weight

2700 kg / 5940 lbs



Loaded weight

2100 kg / 4620 lbs

Speed	Load
6 km/h 3.7 mph	5020 J
8 km/h 5 mph	8880 J
12 km/h 7.5 mph	19960 J

Speed	Load
6 km/h 3.7 mph	3770 J
8 km/h 5 mph	6660 J
12 km/h 7.5 mph	14970 J


Speed	Load
6 km/h 3.7 mph	2930 J
8 km/h 5 mph	5180 J
12 km/h 7.5 mph	11670 J

Component Colours

● RAL 1018 ● RAL 9011

Operating temperature

-10°C → 40°C



1. Bollards

- Classic | 5220 J
- Essential | 1500 J

2. Impact Barriers

- Impact | 4500 J
- Impact High | 6200 J
- Double Impact Low | 7700 J
- Double Impact High | 7000 J

3. Pedestrian Rails

- Pedestrian | 5000 J
- Essential Pedestrian | 2250 J
- Essential Pedestrian 2 rail | 1700 J
- Essential Pedestrian | 2250 J

4. Floor Barrier | 2250 J

- Can be used both with Impact & Pedestrian configurations or as stand-alone protection.

5. Pedestrian Rails + Impact Barriers

- Pedestrian + Impact | 6700 J
- Pedestrian + Impact High | 8000 J
- Pedestrian + Double Impact | 8300 J
- Essential Pedestrian + Impact High | 3100 J

6. Pedestrian Gate | 0 J

7. Column Guard | 1800 J

8. Topple Barriers

- Pedestrian | 5250 J
- Impact | 6200 J

9. Dock Gate | 10200 J

10. Height Restrictors

- Goal Post | 4200 J
- Height Guard

11. Upright Protector