

แม่แบบการเจาะ

เทมเพลตสำหรับเจาะ (Drilling Template) สำหรับผลิตภัณฑ์ X-Protect ได้รับการออกแบบมาโดยเฉพาะเพื่อคงไว้ซึ่งประสิทธิภาพของมาตรการด้านความปลอดภัย เครื่องมือนี้ผลิตอย่างแม่นยำและคำนึงถึงความสะดวกในการใช้งาน ช่วยให้กระบวนการปรับแต่งทำได้ง่ายขึ้น และสามารถปรับความยาวของผลิตภัณฑ์ให้เหมาะกับความต้องการเฉพาะได้โดยไม่กระทบต่อความปลอดภัยหรือประสิทธิภาพ

เครื่องมือนี้ออกแบบมาเพื่อใช้เป็นหลักกับรูปแบบการติดตั้งของราวแบริเออร์กันกระแทก (Impact Barrier) และราวแบริเออร์กันคนเดิน (Pedestrian Barriers)



เทมเพลตสำหรับเจาะ (Drilling Template) ได้รับการออกแบบมาเพื่อให้มั่นใจว่ารูสำหรับพินเซือมต่อจะอยู่ในตำแหน่งที่ถูกต้องและแม่นยำทุกครั้ง ความละเอียดในขั้นตอนนี้ช่วยให้ราวแบริเออร์ยังคงประสิทธิภาพในการป้องกันได้อย่างเต็มที่หลังจากมีการปรับขนาด ช่วยเพิ่มความมั่นใจในความสม่ำเสมอและความน่าเชื่อถือของระบบความปลอดภัย ด้วยเครื่องมือนี้ ช่วยลดความเสียงจากการติดตั้งชิ้นส่วนที่ไม่ตรงแนว รวมถึงความเสียงที่อาจส่งผลต่อความแข็งแรงและประสิทธิภาพของราวแบริเออร์ จึงช่วยรักษามาตรฐานด้านความปลอดภัยในสถานที่ทำงาน

นอกจากนี้ ยังช่วยเพิ่มประสิทธิภาพในการติดตั้งและการปรับแต่งได้อย่างมาก โดยช่วยให้การตัดราวแบริเออร์ให้ได้ตามความยาวที่ต้องการทำได้ง่ายขึ้น เทมเพลตสำหรับเจาะจึงช่วยประหยัดเวลา ลดค่าแรง และลดโอกาสเกิดข้อผิดพลาดในการทำงาน ด้วยการออกแบบที่ใช้งานง่าย จึงสามารถนำไปใช้หน้างานได้อย่างสะดวก ช่วยให้การปรับแต่งทำได้อย่างรวดเร็วและแม่นยำ โดยไม่กระทบต่อความปลอดภัยและช่วยให้โครงการดำเนินไปตามกำหนดเวลา

Models

ARTICLES / DESCRIPTION	
	**RC-DRILL** ชุดแม่แบบเจาะและชุดดอกสว่าน

X-PROTECT

Technical Information

X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Pedestrian Rails



Width x Height:
68 × 72 mm | 2 11/16" × 2 27/32"
Length:
270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:
116 × 220 mm | 4 9/16" x 8 21/32"
Length:
270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Classic
4 connection sides
Width:
200 mm
7 7/8"
Height:
350 – 1160 mm
13 13/16" – 45 11/16"


Essential
2 connection sides
Width:
132 mm
5 3/16"
Height:
620 – 1170 mm
24 7/16" – 46 1/16"




X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding*

* The highest force depends on the C-C. More information is available upon request.






Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight
3600 kg / 7930 lbs

Speed	Load
6 km/h | 3.7 mph	5020 J
8 km/h | 5 mph	8880 J
12 km/h | 7.5 mph	19960 J



Loaded weight
2700 kg / 5940 lbs

Speed	Load
6 km/h | 3.7 mph	3770 J
8 km/h | 5 mph	6660 J
12 km/h | 7.5 mph	14970 J



Loaded weight
2100 kg / 4620 lbs

Speed	Load
6 km/h | 3.7 mph	2930 J
8 km/h | 5 mph	5180 J
12 km/h | 7.5 mph	11670 J

Component Colours

RAL 1018 RAL 9011

Operating temperature

-10°C → 40°C

1. **Bollards**
   - Classic | 5220 J
   - Essential | 1500 J
2. **Impact Barriers**
   - Impact | 4500 J
   - Impact High | 6200 J
   - Double Impact Low | 7700 J
   - Double Impact High | 7000 J
3. **Pedestrian Rails**
   - Pedestrian | 5000 J
   - Essential Pedestrian | 2250 J
   - Essential Pedestrian 2 rail | 1700 J
   - Essential Pedestrian | 2250 J
4. **Floor Barrier** | 2250 J
   - Can be used both with Impact & Pedestrian configurations or as stand-alone protection.
5. **Pedestrian Rails + Impact Barriers**
   - Pedestrian + Impact | 6700 J
   - Pedestrian + Impact High | 8000 J
   - Pedestrian + Double Impact | 8300 J
   - Essential Pedestrian + Impact High | 3100 J
6. **Pedestrian Gate** | 0 J
7. **Column Guard** | 1800 J
8. **Topple Barriers**
   - Pedestrian | 5250 J
   - Impact | 6200 J
9. **Dock Gate** | 10200 J
10. **Height Restrictors**
    - Goal Post | 4200 J
    - Height Guard
11. **Upright Protector**